

SPECYFIKACJA

Audio Inputs (A/D)

Channels	5
Sample Rate	44.1, 48, 88.2, 96 kHz
Bit Resolution	16, 24-bit
Converter	Cirrus Logic

Line Inputs

Full Scale Level	+12.4 dBu
DNR (a-weighted)	98.3 dBu
THD+N	0,05 %
Frequency Response +/-0.5 dB	20 Hz-40 kHz
Cross Talk @ 1kHz	-111dB

Mic Input

Full Scale Level @ 1 kHz	-31.3 dBu
DNR (a-weighted) @ 1 kHz	85.7 dB
THD+N @ 1KHz	0.045 %
Frequency response +/-1.67 dB	20 Hz-20 kHz

Phono Inputs

Input Impedance	47 KOhm
Full Scale Level @ 1 kHz	- 23.5 dBu
DNR (a-weighted) @ 1 kHz	90.2 dB
THD+N @ 1KHz	0,05 %
Crosstalk @ 1kHz	-100 dB

Audio Outputs (D/A)

Channels	4
Sample Rate	44.1, 48, 88.2, 96 kHz
Bit Resolution	16, 24-bit
Converter	Cirrus Logic

Line Outputs (1/4" stereo)

Maximum Output Level	+18 dBu
DNR (a-weighted)	105 dB
THD+N	0,003 %
Frequency Response +/-0.3 dB	20 Hz-40 kHz
Crosstalk @ 1kHz	122dB

Line Outputs (RCA)

Maximum Output Level	+12 dBu
DNR (a-weighted)	105 dB
THD+N	0,002%
Frequency Response +/-0.35 dB	20 Hz-40 kHz
Crosstalk @ 1kHz	-111 dB

Headphone Output

Load Impedance	16 Ohms – 600 Ohms
Maximum Output Level (32 Ohm load)	+2 dBu
DNR (a-weighted)	99.3 dBu
THD+N	0.013 %
Frequency Response +/-1 dB	20 Hz-20 kHz
Crosstalk @ 1kHz	-60 dB